

## Canon SX60 HS Specifications

Megapixels (Effective)	16.1* megapixels * Image processing may cause a decrease in the number of pixels.
Megapixels (Total)	16.8 megapixels
Lens Focal Length	35mm equivalent 21-1365mm
Lens Features	65x Super Zoom with 21mm Wide-angle lens
Aperture Range	f/3.4 - f/6.5
Digital Zoom	4x
Audio	Yes
Burst Mode	Yes (Approx. 6.4 fps)
Compatible Memory Formats	SD, SDHC, SDXC and UHS-I Memory Cards
Exposure Control	Programmed AE, Aperture priority, Shutter priority, Manual ISO Sensitivity : Auto, ISO100-3200 Light Metering Method : Evaluative*, Center-weighted average, Spot*** Facial brightness is evaluated in Face Detection AF** Metering frame is fixed to the center Exposure Control Method : Manual Exposure, AE Lock, Program Shift, Exposure Compensation : (Still Images) 3 stops in 1/3-stop increments, Exposure Shift : (Movie) 2 stops, Flash Exposure Compensation : (Still Images) 2 stops
External Flash Mount (hot shoe)	Yes
Face Detection	Yes
File Formats	JPEG, MP4 (Image data: MPEG-4 AVC/H.264; Audio data: MPEG-4 AAC-LC (Stereo)), RAW
Filter Diameter	67mm *Filter Adapter FA-DC67A is necessary
Flash Modes	Auto, On, Slow Synchro, Off
Flash Range	1.6-18ft.(Wide), 5.9-9.8ft.(Telephoto)

Focus Range	0.0in. - infinity (Wide), 5.9ft. - infinity (Telephoto); Macro: 0.0in. - 1.6ft.(Wide)
Image Resolution	Up to 4608 x 3456
Image Sensor Size	1/2.3"
Image Sensor Type	High Sensitivity CMOS
Image Stabilization	Optical
Image Stitching	No
Interface	Hi-Speed USB ; DIGITAL / audio/video connector(receptacle)HDMI mini connector
ISO Equivalent	Auto, 100 - 3200 ; 6400 in Low Light mode
LCD Screen Features	3.0", Color, TFT-LCD with 922,000 dots resolution, Wide viewing angle
Low-Light / High Sensativity	Canon HS SYSTEM
Movie Mode	Yes
Operating Humidity	32-104 F
Operating Temperature	10-90%
Orientation Sensor	Auto Image Rotation
Panorama Mode	No
PictBridge - compatible	Yes
Scene Modes	C1, C2, M, Av, Tv, P, Hybrid Auto, Auto, Creative Shot, Sports, Portrait, Smart Shutter(Smile, Wink Self-timer, Face Self-timer), Handheld Night Scene, Low Light, Snow, FireworksMovie : Standard, Manual, iFrame Movie, Super Slow Motion Movie Shooting movies is done with the movie button
Self-Timer	Off, 2 sec., 10 sec., Custome Timer* *Wink Self-timer and Face Self-timer modes are

	also available
Shutter Speed	1 - 1/2000 sec.; 15 - 1/2000 sec.(in Tv and M modes)
Smile Mode	Yes
Special Effects	Creative Shot, High Dynamic Range, Fish-eye, Effect, Miniature Effect, Toy Camera Effect, Soft Focus, Monochrome, Super vivid, Poster Effect
Time-Lapse Photography	No
Tripod Mount	Built-In
Video Outputs (A port on most digital ca	NTSC, PAL
Viewfinder	Electronic Viewfinder Approx. 922,000 dots
White Balance Modes	Auto, Day Light, Shade, Cloudy, Tungsten, Fluorescent, Fluorescent H, Flash, Custom 1, Custom 2
Warranty Parts	1 Year Limited
Warranty Term - Labor	1 Year Limited