

| Imaging | |
|-----------------------|--|
| Lens Mount | Fujifilm X Mount |
| Camera Format | APS-C (1.5x Crop Factor) |
| Pixels | Actual: 16.7 Megapixel Effective: 16.3 Megapixel |
| Max Resolution | 4896 x 3264 |
| Sensor Type / Size | CMOS, 23.6 x 15.6 mm |
| File Formats | Still Images: JPEG, RAW Movies: H.264, MOV Audio: Linear PCM (Stereo) |
| Dust Reduction System | Yes |
| Memory Card Type | SD SDHC SDXC |

| AV Recording | |
|---------------------|---|
| Video Recording | Yes |
| Resolution | 1920 x 1080: 60 fps, 30 fps 1280 x 720: 60 fps, 30 fps |
| Aspect Ratio | 16:9 |
| Video Clip Length | Up to 27 Min |
| Audio Recording | Built-in Mic: With Video, Stereo Optional External Mic: With Video |

| Focus Control | |
|----------------------|---------------|
| Focus Type | Auto & Manual |

| | |
|------------------|--|
| Focus Mode | Single-servo AF (S), Continuous-servo AF (C), Manual Focus (M) |
| Autofocus Points | Contrast Detection: 49 |

| Viewfinder/Display | |
|---------------------------|--|
| Viewfinder Type | Electronic |
| Viewfinder Size | 0.5" |
| Viewfinder Pixel Count | 2,360,000 |
| Viewfinder Eye Point | 23.00 mm |
| Viewfinder Coverage | 100% |
| Viewfinder Magnification | Approx. 0.77x |
| Diopter Adjustment | - 4 to +2 m |
| Display Screen | 3" Rear Screen Tilting LCD (1,040,000) |
| Screen Coverage | 100% |

| Exposure Control | |
|-------------------------|---|
| ISO Sensitivity | Auto, 200-6400 (Extended Mode: 100-51200) |
| Shutter | Type: Electronic & Mechanical Speed: 30 - 1/4000 sec Type: Electronic & Mechanical Speed: 1/4 - 1/4000 sec in Program Mode Type: Electronic & Mechanical Speed: 60 - 0 min in Bulb Mode Type: Electronic & Mechanical Speed: 30 - 1/2 sec in Time Mode |
| Remote Control | RR-90 (Optional) |
| Metering | Average metering, Multi-zone metering, Spot metering |

| | |
|---------------------|---|
| Method | |
| Exposure Modes | Modes: Aperture Priority, Manual, Programmed Auto, Shutter Priority Compensation: -3 EV to +3 EV (in 1/3 EV steps) |
| White Balance Modes | Automatic Scene Recognition, Color Temperature, Custom, Fine, Fluorescent (Cool White), Fluorescent (Daylight), Fluorescent (Warm White), Incandescent, Shade, Underwater |
| Burst Rate | Up to 8 fps at 16.3 MP for up to 47 frames Up to 3 fps at 16.3 MP |

| | |
|---------------------------|--|
| Flash | |
| Flash Modes | Auto Auto/Red-eye Reduction Commander Commander/Red-eye Reduction Forced On Forced On/Red-eye Reduction Rear Curtain Sync/Red-eye Reduction Rear Sync Slow Sync Slow Sync/Red-eye Reduction Suppressed Flash |
| Max Sync Speed | 1 / 180 sec |
| Dedicated Flash System | TTL |
| External Flash Connection | Hot Shoe, PC Terminal |

| | |
|---------------------|---------------|
| Performance | |
| Start-up Time | 0.5 Seconds |
| Shutter Lag | 0.05 Seconds |
| Continuous Shooting | Up to 8 fps |
| Self Timer | 10 sec, 2 sec |

| | |
|------------------------------|--|
| Interval Recording | Yes |
| Connectivity | 2.5mm Sub-mini (2-Ring), HDMI C (Mini), USB 2.0, X-Sync Socket |
| Wi-Fi Capable | Yes |
| Software System Requirements | Windows: XP, Vista, 7, 8 Mac: OS X 10.6, 10.7, 10.8 |

| | |
|-------------------------------|---|
| Power | |
| Battery | 1x NP-W126 Rechargeable Lithium-Ion Battery Pack, 7.2VDC, 1260mAh |
| Operating/Storage Temperature | Operating 14 to 104°F (-10 to 40°C) Humidity: 10 - 80% |

| | |
|--------------------|--|
| Physical | |
| Dimensions (WxHxD) | 5.1 x 3.5 x 1.8" / 129.0 x 89.8 x 46.7 mm <i>Minimum depth: 1.3" / 33.4 mm</i> |
| Weight | 15.52 oz / 440 g <i>with battery and memory card</i> |

| | |
|------------------------|------------------|
| Packaging Info | |
| Package Weight | 2.7 lb |
| Box Dimensions (LxWxH) | 8.9 x 7.9 x 4.1" |